

# Ball Valve

DN 2" - 10"  
ASME Class 150 - 1500




INNO-BALL

## Design

Split-body ball valve.  
Trunnion mounted ball.  
With soft seats or metal seats.  
With full bore or reduced bore  
Actuator attachment acc. to DIN ISO 5211.

OPTIONAL GEAR OPERATOR



## Dimensions (in mm)

Size DN FB	2"	3"	4"	6"	8"	10"
Size DN RB	-	3"x2"	3"x4"	6"x4"	8"x6"	10"x8"
Bore FB/RB	50/-	75/50	100/75	150/100	201/150	252/201
(Class 150) - L	178	203	229	394	457	533
(Class 300) - L	216	283	305	403	502	568
(Class 600) - L	292	356	432	559	660	787
(Class 900) - L	368	381	457	610	737	838
(Class 1500) - L	368	470	546	705	832	991
H1 (max)	175	207	237	305	359	415
H2 (max)	67	82	95	148	200	225
Lo (max)	450	600	1000	1000	1000	1000
(Class 150) - Weight (kg)	12	23	32	98	166	355
(Class 300) - Weight (kg)	15	31	46	110	170	400
(Class 600) - Weight (kg)	30	44	90	160	230	490
(Class 900) - Weight (kg)	50	85	140	350	560	810
(Class 1500) - Weight (kg)	49	110	182	390	650	960

